



FIXNORDIC.DK

Roof Console Directfix 2-layer From Fixnordic



DATASHEET

Roof Console Directfix 2-layer
From Fixnordic



PRODUCTDESCRIPTION:

Fixnordic Roof Console Directfix 2-layer

The Roof Console DirectFix with 2-layers of bitumen has been developed based on market experiences and constructive customer feedback and is targeted for application onto flat roof surfaces with 2-layer bituminous roof coverings.

APPLICATION AND LOAD CAPACITY:

The precondition for a correct application of the Roof Console DirectFix is that a qualified analysis is conducted of the various loads (wind, snow, cold and heat) which will impact each console throughout the expected life time of the installation. It's crucial that the analysis focuses on the complete system and hereby including elements such as: The roof deck, the VCL, insulation thickness, etc. Fixnordic recommends that the load design is performed either by the system-suppliers, mounting-system suppliers, solar contractors, consultancy engineers or architects and points out, that Fixnordic is available to assist in this process.

If the Roof Console DirectFix is used as a part of a complete solar installation where Fixnordic has made the load design of the mounting system including fixation, the specific console configuration with corresponding load calculations will be a part of the standard project documentation.

ORDERING:

TYPE	ITEM
ROOF CONSOLE DIRECTFIX 2-LAYER	230062-1XX Art. No. - Membrane No
Find the Membrane overview under "Downloads" on fixnordic.dk	



General Installation Guidelines

For further information concerning anchor types for the DirectFix Roof Console please refer to the present application matrix or contact Fixnordic.

APPLICATION

The Console DirectFix product has been made with the purpose of achieving an effective, safe and simple systematic solution for the fixation of fully covering solar installations on flat roofs where technical requirements have been set with the target of utilizing materials and resources in the most efficient way for this type of installations. The product has, as the present range of console products, been developed in a close cooperation with the roofing industry under consideration of the present industry guidelines and intentions.

INSTALLATION

The first step in the installation process of installing the Roof Console DirectFix is to install the chosen Console Anchor on to which the console is connected by engaging the Anchor into the internal M12 tread of the Connection-element. When the console has been turned until it aligns smoothly with the surface of the roof, the console position is slightly adjusted until the intended membrane orientation relative to the roof is reached and the first membrane layer is hereafter fully welded and followed by the welding of the top layer. Fixnordic recommends that Roof Consoles with a square formed membrane is oriented with one corner facing up against the inclination of the roof in order to ensure a smooth draining of the roof surface.

For further information about specific installation details please refer to the present installation guidelines.

Regarding the welding of roof membranes JUAL SOLAR recommends that this work is carried out by educated roofers who have been trained to work with the specific membrane at hand.